Response Under 37 C.F.R. 1.116 (After Final) **Expedited Procedure Examining Group 2833**

Attorney Docket Number: DELRI/109/US

Serial Number: 10/091,730

CI EAN COPY OF THE AMENDED PORTIONS OF THE APPLICATION

In the Claims

Please amend claims 1, 9, and 15 as indicated below.

A ground connector for use with an associated distribution transformer which 1.

comprises:

a one piece base comprising a fixed jaw, a first guide portion and a spade

connector defining an opening; and

a one piece movable member comprising a movable jaw, a second guide portion

partially defining a receiving cavity, said receiving cavity configured for receiving said

first guide portion in sliding engagement in order to guide longitudinal movement of said

movable member with respect to said base to form a clamp, said first guide portion and

said second quide portion, having a pair of opposing ribs and a pair of opposing

channels which cooperate with said ribs; and

securement means for securing said base and movable member so that when a

cable is received between said fixed jaw and said movable jaw, said jaws are securably

clampable against said cable.

9. A ground connector installation comprising:

a distribution transformer, having a generally cylindrical shaped housing and

having a ground connecting means;

a one piece base comprising a fixed jaw, a first guide portion, and a spade

connector defining an opening;

a one piece movable member comprising a movable jaw, a second guide portion,

and a receiving cavity, said receiving cavity at least partially defines the second guide

17

Response Under 37 C.F.R. 1.116 (After Final) Expedited Pr cedure Examining Gr up 2833

Attorney Dock t Number: DELRI/109/US

portion, and receives the first guide portion wherein said first guide portion and said second guide portion are configured for sliding engagement to guide longitudinal movement of said movable member with respect to said base to form a clamp, said first guide portion and said second guide portion having a pair of opposing ribs and a pair of opposing channels which cooperate with said ribs; and

securement means for securing said base and movable member so that when a cable is received between said fixed jaw and said movable jaw, said jaws are securably clampable against said cable; and

a bolt extending through said opening into said ground connecting means for mounting said base to said transformer.

15. The ground connector of claim 14, wherein said cable is secured in said clamp in an orientation which is perpendicular to a direction of said longitudinal movement of said movable member with respect to said base.